










Technical Data Sheet

WAX AND GREASE REMOVER

	<p>Description</p> <p>50141 WAX & GREASE REMOVER 1GL 50145 WAX & GREASE REMOVER 5GL</p> <p>Hoseki Wax & Grease Remover is a premium, fast-drying solvent blend engineered to lift and eradicate wax, silicone, oil, grease, and other surface contaminants. It flashes off quickly to leave a perfectly clean, residue-free surface. It is the ultimate pre-paint prep solution compatible with virtually any substrate, including metal, fiberglass, plastic, and existing painted finishes</p>
	<p>Surface Preparation</p> <p>N/A</p>
	<p>Mixing Directions</p> <p>This product is supplied completely ready to use. No reduction or activation is required.</p>

	<p>Application</p> <p>Apply prior to any grinding, sanding, or painting to prevent contaminants from being ground into the substrate. Apply directly to the surface and wipe immediately with a clean, dry cloth. Work in small sections, rubbing the surface briskly. Change wiping cloths frequently to prevent spreading contaminants across the panel. For optimal results, manually wipe the surface completely dry. Do not allow the solvent to naturally evaporate or air-dry on the panel.</p>
	<p>Bake Time</p> <p>N/A</p>
	<p>Dry Time</p> <p>N/A</p>
	<p>Temperature Guidelines</p> <p>N/A</p>
	<p>Suitable Substrates</p> <p>Bare steel, bare aluminum, and bare galvanized metal All OEM finishes 1K, 2K, and self-etching primers Primed plastic parts and OEM E-Coat Body filler Note on Plastics: Automotive plastics vary widely, so always test a small area for acceptable adhesion prior to full application.</p>
	<p>Additives</p> <p>N/A</p>



Personal Protection

For use only by professional, trained painters. Not for sale to or use by the general public. Before use, read and follow all TDS, label, and Safety Data Sheet (SDS) precautions. This product contains hazardous materials and must be used with appropriate personal protective equipment (PPE), including a NIOSH-approved respirator, safety glasses, and chemical-resistant gloves. If mixed with other components, the resulting mixture will have the hazards of all combined components. Ensure adequate ventilation during mixing, application, and curing processes.



Technical Data

Color: Clear
Shelf Life: 5 years
Mix Ratio: Ready to Use
Weight % of Volatiles: 100%
Weight % of Water: 0%
Weight % of Exempt Compounds: 0%
Actual VOC: 5.84 lbs./gal. (700 g/L)
Regulatory VOC: 5.84 lbs./gal. (700 g/L)
Density: 5.84 lbs./gal.
Product Category: Cleaner