










Technical Data Sheet

FISHEYE ELIMINATOR

	<p>Description</p> <p>70022 FISHEYE ELIMINATOR 1PT. 70024 FISHEYE ELIMINATOR 1QT.</p> <p>Hoseki Fisheye Eliminator is a specialized additive formulated to help avoid and prevent fisheyes caused by surface contamination. It is compatible with virtually all types of urethane and non-urethane 2K topcoats to ensure a flawlessly smooth final finish.</p>
	<p>Surface Preparation</p> <p>N/A</p>
	<p>Mixing Directions</p> <p>Mix directly with Hoseki 2K Clearcoats or 2K Primers. Add 1/4 to 1/2 ounce of Hoseki Fisheye Eliminator per sprayable quart.</p>

	<p>Application</p> <p>Because this is a system additive, you must refer to the specific Technical Data Sheet (TDS) of the Hoseki topcoat or primer being applied for proper surface preparation and application instructions.</p>
	<p>Bake Time</p> <p>N/A</p>
	<p>Dry Time</p> <p>N/A</p>
	<p>Pot Life</p> <p>N/A</p>
	<p>Suitable Substrates</p> <p>N/A</p>
	<p>Additives</p> <p>N/A</p>



Personal Protection

For use only by professional, trained painters. Not for sale to or use by the general public. Before use, read and follow all TDS, label, and Safety Data Sheet (SDS) precautions. This product contains hazardous materials and must be used with appropriate personal protective equipment (PPE), including a NIOSH-approved respirator, safety glasses, and chemical-resistant gloves. If mixed with other components, the resulting mixture will have the hazards of all combined components. Ensure adequate ventilation during mixing, application, and curing processes.



Technical Data

Color: Clear
Shelf Life: 3 years
RTS Solids: 13.01%
Weight % of Volatiles: 86.99%
Weight % of Water & Exempt Compounds: 0%
Actual VOC: 6.52 lbs./gal. (781 g/L)
Regulatory VOC: 6.52 lbs./gal. (781 g/L)
Density: 7.50 lbs./gal.
Product Category: System Additive